

Pore size effects on physicochemical properties of Fe-Co/K-Al₂O₃ catalysts and their catalytic activity in CO₂ hydrogenation to light olefins

Thanapha Numpilai^{ab}, Narong Chanlek^c, Yingyot Poo-Arporn^c, Suttipong Wannapaiboon^c, Chin Kui Cheng^d, Nuchanart Siri-Nguan^e, Thana Sornchamni^e, Paisan Kongkachuichay^{ab}, Metta Chareonpanich^{ab}, Günther Rupprechter^f, Jumras Limtrakul^g, Thongthai Witoon^{abg}

^a Center of Excellence on Petrochemical and Materials Technology, Department of Chemical Engineering, Faculty of Engineering, Kasetsart University, Bangkok 10900, Thailand

^b Research Network of NANOTEC–KU on NanoCatalysts and NanoMaterials for Sustainable Energy and Environment, Kasetsart University, Bangkok 10900, Thailand

^c Synchrotron Light Research Institute, Nakhon Ratchasima 30000, Thailand

^d Faculty of Chemical & Natural Resources Engineering, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300 Gambang Kuantan, Pahang, Malaysia

^e Innovation Institute, PTT Public Company Limited, Phra Nakhon Si Ayutthaya 13170, Thailand

^f Institute of Materials Chemistry, Technische Universität Wien, Getreidemarkt 9/BC/01, Vienna 1060, Austria

^g Department of Materials Science and Engineering, School of Molecular Science and Engineering, Vidyasirimedhi Institute of Science and Technology, Rayong 21210, Thailand

ABSTRACT

In this work, the hydrogenation of CO₂ to light olefins has been studied over the Fe-Co/K-Al₂O₃ catalysts, while focusing on the impact by the pore sizes of Al₂O₃ supports including 6.2 nm (S-Al₂O₃), 49.7 nm (M-Al₂O₃) and 152.3 nm (L-Al₂O₃) on the structure and catalytic performance. The characterization results demonstrate that the pore sizes of the Al₂O₃ supports play a vital role on the crystallite size of Fe₂O₃, the reducibility of Fe₂O₃ and the adsorption-desorption of CO₂ and H₂. The catalyst with the smallest pore size (CS-Al₂O₃) allows the formation of a small Fe₂O₃ crystallite size due to pore confinement effects, yielding a low active component (Fe) after reduction at 400 °C for 5 h. The catalysts with the larger pore sizes of 49.7 nm (CM-Al₂O₃) and 152.3 nm (CL-Al₂O₃) provide the larger Fe₂O₃ crystallite sizes which require a longer reduction time for enhancing degree of reduction, resulting in a high metallic Fe content, leading to a high CO₂ conversion and a high selectivity toward hydrocarbon. Eliminating diffusion limitation by increasing the pore sizes of Al₂O₃ supports can suppress the hydrogenation of olefins to paraffins and thus the largest pore catalyst (CL-Al₂O₃) gives the highest olefins to paraffins ratio of 6.82. Nevertheless, the CL-Al₂O₃ also favors the formation of C₅₊ hydrocarbon. Therefore, the highest light olefins yield (14.38%) is achieved over the catalyst with appropriated pore size (CM-Al₂O₃).

KEYWORDS

Light olefins; CO₂ hydrogenation; Fe-based catalysts; Al₂O₃; Pore sizes

ACKNOWLEDGMENTS

This work was financially supported by the Thailand Research Fund(grant no. RSA6280007), the Center of Excellence on Petrochemical and Materials Technology (PETROMAT), the Nanotechnology Center (NANOTEC), NSTDA, the Ministry of Science and Technology of Thailand, through its program of Research Network of NANOTEC (RNN), the Kasetsart University Research and Development Institute(KURDI), and The Capacity Building of KU Students on Internationalization Program. BL1.1W Multiple X-ray Techniques at the Synchrotron Light Research Institute (SLRI), Thailand is acknowledged for the facilities and the beamtime for 2D-XRD measurement.